



Outdoor Multi-tap 55 Series 1 GHz Features:

- 5-1002 MHz bandwidth
- 15 Amp current capacity
- Blocking capacitors on the "F" ports for extended surge resistant SR
- Power passing option: CB: continuous through signal w/o faceplate
- Aluminum alloy housing used for corrosion resistant
- Double polyurethane coating for greater weather protection
- Rubber gasket and RFI shielding gasket
- Epoxy sealed and nickel plated brass ports
- Printed circuit board
- Easy interchangeable 2/4 port faceplates
- Aerial or pedestal installation
- Rotational seizure mechanism for aerial or pedestal installation
- Compliant with SCTE guidelines

	Std Ctn Qty	Inner Box	Box Weight	xx dB Values
DT55G-SR-CB-2xx Series	50 pcs	10 pcs	17 kgs	-04T,-08,-11,-14,-17,-20,-23,-26,-29,-32
DT55G-SR-CB-4xx Series	50 pcs	10 pcs	18 kgs	-08T,-11,-14,-17,-20,-23,-26,-29,-32,-35
DT55G-SR-CB-8xx Series	40 pcs	10 pcs	21 kgs	-11T,-14,-17,-20,-23,-26,-29,-32,-35
DT55G-SR-CB-82xx Series	40 pcs	10 pcs	21 kgs	-04T,-08,-11,-14,-17,-20,-23,-26,-29,-32,-35
DT55G-SR-CB-84xx Series	40 pcs	10 pcs	21 kgs	-08T,-11,-14,-17,-20,-23,-26,-29,-32,-35
DC55G-xx Series	30 pcs	10 pcs	20 kgs	-2,-3,-3B Splitter, -8,-12,-16 dB Coupler, -PI Power Inserter

